



CATALOG NUMBER	LENGTHS L (INCHES)	ULTIMATE MECHANICAL STRENGTHS (LBS)		
		ANCHORING EYE	LONGITUDINAL L1	TRANSVERSE T
GDAS36H	36	25,000	12,000	10,000
GDAS38H	38	25,000	11,000	10,000
GDAS42H	42	25,000	10,000	10,000
GDAS48H	48	25,000	9,500	10,000
GDAS54H	54	25,000	9,000	10,000
GDAS60H	60	25,000	8,500	10,000
GDAS72H	72	25,000	7,000	10,000

- ① TO SPECIFY EYELET ATTACHMENT HARDWARE (PER DETAIL 1) ADD SUFFIX "B2".
(EXAMPLE: FOR 48 INCH LENGTH W/ EYELET'S: GDAS48HB2)
- ② TO SPECIFY EYELET ATTACHMENT HARDWARE (PER DETAIL 2) ADD SUFFIX "N4".
(EXAMPLE: FOR 60 INCH LENGTH W/ EYELET'S: GDAS60HN4)

NOTES:

- 1.0 MATERIAL
 - 1.1 BASE - DUCTILE IRON 654512
 - 1.2 END FITTING - A356-T6 ALUMINUM ALLOY
 - 1.3 ROD - FIBERGLASS
 - 1.4 HARDWARE - STEEL
- 2.0 FINISH
 - 2.1 BASE - HOT DIP GALV. PER ASTM A-153
 - 2.2 END FITTING - NONE
 - 2.3 ROD - VULCANIZED SILICONE RUBBER, GRAY
 - 2.4 HARDWARE - HOT DIP GALV. PER ASTM-A153
- 3.0 DIMENSIONS IN INCHES

3	09-20-21	REMOVE PAINT OPTION	BHB
3	05-25-17	ADDED 72" SIZE.	MBG
2	11-05-14	ADDED 38" SIZE.	WCL
1	7-05-12	ADDED DETAIL 2 DOUBLE EYE NUTS FIG.	MYL
NO.	DATE	DESCRIPTION	BY

Maclean Power Systems
Continental Electric
 PO Box 835, Trussville, AL 35173
 Phone: (205)855-7400 Fax: (205)855-3530

DRAWN BY: MW	APPROVED BY:	SCALE: NONE
	CHECKED BY:	

GDAS-"L"-H SERIES
ROUND SOLID DEADEND CROSSARM ASSEMBLY

DATE: 08-14-02	DRAWING NO: CEB-3594	SH: 1	R: 4
		OF: 1	

PROPRIETARY
 This information is confidential and is the property of Maclean Power Systems. It may not be made public or reproduced except that the customer may make copies for use solely in the installation, maintenance, and operation of products supplied by Maclean power systems.