

MPS Catalog Number:

S6 40 80 072 VA SS 042

Date:

05/11/2021

End Fittings

Tower End Fitting:

Y-Clevis

Line End Fitting:

Ball (IEC 20)

Material

Corona Ring (Tower):

None

Corona Ring (Line):

8" Corona Ring

Corona Rings are recommended for applications of 230 kV and above

Number of Sheds:

42 Standard

Rod Diameter:

18 mm

Weight Estimate:

21.3 lbs

10 kg

Dimensional Values

Section Length (L):

85.4 in 2,169 mm

Rubber Length (X):

72 in 1,829 mm

Standard Shed Height (P):

2.2 in 55 mm

Shed Spacing (S):

1.71 in 43 mm

Dry Arc Distance:

72.1 in 1,831 mm

Leakage Distance:

233.7 in 5,936 mm

Electrical Values

60 Hz dry Flashover (Min. Withstand):

701 kV 637 kV

60 Hz Wet Flashover (Min. Withstand):

608 kV 529 kV

CIFO Positive (Min. Withstand):

1175 kV 1040 kV

CIFO Negative (Min. Withstand):

1232 kV 1097 kV


Mechanical Values

Specified Mech. Load (SML):

36,000 lbs 160.1 kN

Routine Test Load (RTL):

18,000 lbs 80.1 kN



Dimension: inches [millimeters]

NOTE: Drawing not actual depiction of insulator appearance.

Silicone rubber sheath and sheds complies with applicable ANSI and IEC standards.

Notes:

Prepared By: Laurel Wallace