

## Suspesion Corona Ring Family


MPS Smart Fit Corona Rings come in three standard sizes; 8", 12", & 17", and are designed for use on all "VX" and "MX" Series Suspension Insulators.



Recommended Corona Ring Applications								
	115kV	138kV	161kV	230kV	345kV		500kV	765kV
Catalog Ref.	X	X	А	А	В	G	V	Н
Line End	*	*	8"	8"	12"	12"	17"	17"
Tower End	_	_	_	_	_	8"	8"	12"
Stacked Shed	SS	SS	SS	SS	SS / EHV		EHV	UHV

<sup>\* 8&</sup>quot; Corona Ring available if required by customer or to satisfy modeling


Note: A 8" corona ring is desirable at 161kV, but must have CR at ≥ 230kV
The corona ring is a part of the suspension catalog number
To include an 8" CR, change VX to VA or MX to MA4
Adding a corona ring will reduce the dry arc distance 1.5" to 3.0"



## **Features**

- Unidirectional Fit
- · Located onto Corona Ball
- 2 Piece Keeper System
- Maximum Protection
- Easy Installation
- · Hot Stick Workable

## Smart Fit Corona Ring Installation



Step 1: Open Keepers

Step 2: Fit Onto Corona Ball

Step 3: Close & Tighten