


1 1/2" Square Shaft Lead Anchors

Features

- 1 1/2" square solid shaft power shaft screw anchors are used in areas where additional helices must be installed and greater torque capacity is required
- There are two ratings a standard with 5,500 ft/lbs and a high strength with 7,000 ft/lbs ultimate torque capacity
- Ultimate anchor holding strength and mechanical strength (lead section, extension, guy adapter) is 70,000 lbs





5,500 Ft/Lb Ultimate Installing Torque			
Catalog Number	5		Wt Ea (Lb)
D6632	8 & 10	3.0	34
D6634	10 & 12	3.5	48
D6635	8, 10, 12 & 14	10.5	126
D6636	8, 10 & 12	5.5	65
D6637	10, 12, & 14	7.0	91
D6638	10, 12, 14 & 14	10.5	137

Notes:

1) Catalog numbers above are for lead section only

 Add suffix "-SU" for single guy eye attachment; add "-DU" for double guy eye attachment; add suffix "-TU" for triple guy eye attachment (i.e. D6632SU)

1 1/2" Square Extensions

- Features
- Extensions with helix for additional helices
- Extensions range from 3.5' to 10' in length
- The extension torque rating must match the lead section

1 1/2" Square Shaft Extension With Helix

C	
	/
	9

e

5,500 Ft/Lb Ultimate Installing Torque			
Catalog Number	Helix Size (In)	Length (Ft)	Wt Ea (Lb)
D6620UC	12	-	52.4
D6620UD	14 5		56.5

1 1/2" Square	Shaft Extension
Without Helix	

5,500 Ft/Lb Ultimate Installing Torque		
Catalog Number	Length (Ft)	Wt Ea (Lb)
D6616U	3.5	28.2
D6620U	5	39.9
D6625-U	7	56.8
D6630-U	10	81.0



1 1/2" Guy Attachments Features

Available in single guy eye, double guy

eye, or triple guy eye

Catalog Number	No. of Guys	Wt Ea (Lb)
D6602US	1	
D6604US	2	9.2
D6606US	3	



1 1/2" Square Shaft Lead Anchors Features

- 1 1/2" square solid shaft power shaft screw anchors are used in areas where additional helices must be installed and greater torque capacity is required
- There are two ratings a standard with 5,500 ft/lbs and a high strength with 7,000 ft/lbs ultimate torque capacity
- Ultimate anchor holding strength and mechanical strength (lead section, extension, guy adapter) is 70,000 lbs





7,000 Ft/Lb Ultimate Installing Torque				
Catalog Number	Helix Size Length Wt Ea (in) (ft) (lb)			
D6632-7	8 & 10	3.0	34	
D6634-7	10 & 12	3.5	48	
D6636-7	8, 10 & 12	5.5	65	
D6637-7	10, 12, & 14	7.0	91	

Notes:

 Catalog numbers above are for lead section only
Add suffix "-SU" for single guy eye attachment; add "-DU" for double guy eye attachment; add suffix "-TU"

for triple guy eye attachment (i.e. D6632SU7)

1 1/2" Square Extensions

Features

- Extensions with helix for additional helices
- Extensions range from 3.5' to 10' in length
- The extension torque rating must match the lead section

1 1/2" Square Shaft Extension With Helix

7,000 Ft/Lb Ultimate Installing Torque			
Catalog Number	Helix Size (in)	Length (ft)	Wt Ea (lb)
D6616UC7	12	2.5	40.6
D6616UD7	616UD7 14 3.5		49.0

1 1/2" Squar	e Shaft Extension
Without Helix	

7,000 Ft/Lb	7,000 Ft/Lb Ultimate Installing Torque		
Catalog Number	Length (ft)	Wt Ea (Ib)	
D6616U7	3.5	28.2	
D6620U7	5	40.7	
D6625U7	7	56.8	
D6630U7	10	81.0	



1 1/2" Guy Attachments Features

• Available in single guy eye, double guy eye, or triple guy eye

Catalog Number	No. of Guys	Wt Ea (Lb)
D6602US	1	
D6604US	2	9.2
D6606US	3	