

# Round









# Material

Galvanized Steel

Catalog Number	OD	Hole Dia	Bolt Dia	Thickness	Weight/ 100 (lbs)
J1084	1	7/16	3/8	0.083	1.5
J1086	1 3/8	9/16	1/2	0.109	3.1
J1088	1 3/4	11/16	5/8	0.134	6.5
J1089	2	13/16	3/4	0.148	9.5

# Spring, Formed Steel

Spring formed steel washers are used to keep units in tension when wood crossarm or wood pole shrinkage occurs.

# Features

• Designed to enable the nut of a bolt to seat flat on the spring washer surface when it is compressed

# Material

Steel hot dip galvanized

Catalog Number	Bolt Dia	Material Size	Formed Length	с	Weight/ 100 (lbs)
J3539	1/2	3/16 x 1	2 7/16	1/2	23
J3540	5/8	1/4 x 1 3/4	3 3/4	9/16	90
J3541	3/4	1/4 x 1 3/4	3 3/4	9/16	88
J3542	7/8	1/4 x 1 3/4	3 3/4	9/16	96
J3543	1	1/4 x 1 3/4	3 3/4	9/16	92

# Spring Lock, Single Coil

### Features

• Made of high grade spring steel to keep a bolt nut in tension, insuring a tight assembly under all temperatures

### Material

Steel hot dip galvanized

Catalog Number	Size (in)	Bolt Dia	Weight/ 100 (lbs)
J134	0.141 x 0.094	3/8	0.8
J138	0.171 x 0.125	1/2	2.0
J139	0.203 x 0.156	5/8	2.7
J140	0.234 x 0.188	3/4	4.5

# Spring Lock, Double Coil

Double coil spring lock washers compensate for wood shrinkage to help eliminate radio interference caused by loose hardware.

## Material

**PH-126** 

Steel hot dip galvanized

Catalog Number	Size (in)	Bolt Dia	Weight/ 100 (lbs)
J175	0.141 x 0.094	3/8	1.1
J176	0.171 x 0.125	1/2	3.2
J177	0.203 x 0.156	5/8	4.1
J178	0.234 x 0.188	3/4	7.0

