Clamps





Cable Suspension, Angle


Features

- Angle suspension clamps have curved ends to prevent damage to the messenger strand when turning small angles
- All clamps firmly grip 1/4 to 7/16" diameter strand
- They are furnished with two track bolts and a center mounting hole

Material

Steel hot dip galvanized

| Catalog Number | Clamp Bolt Dia. | Clamp Length | Clamping Width (in) | Mounting Hole Dia. | Weight /100 (lbs) |
|-------------------|--------------------|-----------------|------------------------|-----------------------|----------------------|
| J7901 | 1/2 | 5 3/4 | 1 11/16 | 13/16 | 208 |
| J7901A | 1/2 | 5 3/4 | 1 11/16 | 11/16 | 210 |
| J7902B | 5/8 | 6 | 2 3/16 | 13/16 | 385 |



Crossover

Features

- Used to clamp on two messengers where they cross at right angles to prevent wear and abrasion
- The J7930 clamp sections are 1 1/2" wide and 3 1/4" long
- Two 1/2" diameter bolts have oval shoulders to prevent turning when tightening

Material

Ductile iron hot dip galvanized

| Catalog | Strand Dia. | Weight | |
|---------|-------------|------------|--|
| Number | Range | /100 (lbs) | |
| J7930 | 1/4 - 3/8" | 154 | |