

MPS Catalog Number:  
Date:

S1 40 80 066 VX SS 036  
09/03/2013

**END FITTINGS**

Tower End Fitting: Y-Clevis  
Line End Fitting: Ball (ANSI 52-5)

**MATERIAL**

Corona Ring (Tower): None  
Corona Ring (Line): None  
Corona Rings are recommended for applications of 230 kV and above  
Number of Sheds: 36 standard  
Rod Diameter: 16 mm  
Weight Estimate: 16 lbs 7.3 kg

**DIMENSIONAL VALUES**


Section Length (L): 77.2 in 1,961 mm  
Rubber Length (X): 66 in 1,665 mm  
Standard Shed Height (P): 2.1 in 54 mm  
Shed Spacing (S): 1.83 in 46 mm  
Dry Arc Distance: 69.2 in 1,758 mm  
Leakage Distance: 204 in 5,182 mm

**ELECTRICAL VALUES**

60 Hz Dry Flashover: 673 kV Min. Withstand: 614 kV  
60 Hz Wet Flashover: 586 kV Min. Withstand: 510 kV  
Pos. Critical Impulse Flashover: 1,131 kV Min. Withstand: 1,000 kV  
Neg. Critical Impulse Flashover: 1,188 kV Min. Withstand: 1,029 kV

**MECHANICAL VALUES**

Specified Mech. Load (SML): 25,000 lbs 111.2 kN  
Routine Test Load (RTL): 12,500 lbs 55.6 kN



This drawing contains confidential information that is property of MacLean Power L.L.C ('MacLean'). Use of MacLean's confidential information without MacLean's express written consent is strictly prohibited and may expose you to legal liability. If you believe that you received this material in error, please destroy it or return it to 'MacLean Power, L.L.C., 7801 Park Place Rd, York, SC, 29745, USA.'

Dimensions: inches [millimeters]  
Note: Drawing not actual depiction of insulator appearance

Silicone Rubber Sheath & Sheds  
Complies with applicable ANSI and IEC standards.