

MPS Catalog Number:

S1 40 80 090 VA SS 026

Date:

09/04/2013

END FITTINGS

Tower End Fitting:

Y-Clevis

Line End Fitting:

Ball (ANSI 52-5)

MATERIAL

Corona Ring (Tower):

None

Corona Ring (Line):

8" Corona Ring

Corona Rings are recommended for applications of 230 kV and above

Number of Sheds:

26 standard

Rod Diameter:

16 mm

Weight Estimate:

16.6 lbs

7.5 kg

DIMENSIONAL VALUES


Section Length (L):	101.2 in	2,570 mm
Rubber Length (X):	90 in	2,275 mm
Standard Shed Height (P):	2.1 in	54 mm
Shed Spacing (S):	3.75 in	95 mm
Dry Arc Distance:	89.7 in	2,278 mm
Leakage Distance:	189.2 in	4,806 mm

ELECTRICAL VALUES

60 Hz Dry Flashover:	869 kV	Min. Withstand:	779 kV
60 Hz Wet Flashover:	733 kV	Min. Withstand:	638 kV
Pos. Critical Impulse Flashover:	1,435 kV	Min. Withstand:	1,288 kV
Neg. Critical Impulse Flashover:	1,497 kV	Min. Withstand:	1,317 kV

MECHANICAL VALUES

Specified Mech. Load (SML):	25,000 lbs	111.2 kN
Routine Test Load (RTL):	12,500 lbs	55.6 kN



This drawing contains confidential information that is property of MacLean Power L.L.C ('MacLean'). Use of MacLean's confidential information without MacLean's express written consent is strictly prohibited and may expose you to legal liability. If you believe that you received this material in error, please destroy it or return it to 'MacLean Power, L.L.C., 7801 Park Place Rd, York, SC, 29745, USA.'

Dimensions: inches [millimeters]

Note: Drawing not actual depiction of insulator appearance

Silicone Rubber Sheath & Sheds
Complies with applicable ANSI and IEC standards.