

MPS Catalog Number:

S1 90 90 025 MA AL 015

Date:

01/23/2014

**END FITTINGS**

Tower End Fitting:

Eye (Forged Steel)

Line End Fitting:

Eye (Forged Steel)

**MATERIAL**

Corona Ring (Tower):

None

Corona Ring (Line):

8" Corona Ring

Corona Rings are recommended for applications of 230 kV and above

Number of Sheds:

7 large 8 standard

Rod Diameter:

16 mm

Weight Estimate:

9.7 lbs 4.4 kg

**DIMENSIONAL VALUES**

Section Length (L):

37.9 in 963 mm

Rubber Length (X):

24.5 in 622 mm

Standard Shed Height (P1):

1.5 in 38 mm

Large Shed Height (P2):

2 in 51 mm

Projection Ratio (S/P):

- 1.5

Shed Spacing (S):

3 in 76 mm

Dry Arc Distance:

24.2 in 615 mm

Leakage Distance:

66.9 in 1,699 mm

**ELECTRICAL VALUES**

60 Hz Dry Flashover:

245 kV Min. Withstand: 228 kV

60 Hz Wet Flashover:

220 kV Min. Withstand: 192 kV

Pos. Critical Impulse Flashover:

425 kV Min. Withstand: 366 kV

Neg. Critical Impulse Flashover:

458 kV Min. Withstand: 407 kV

**MECHANICAL VALUES**

Specified Mech. Load (SML):

25,000 lbs 111.2 kN


Routine Test Load (RTL):

12,500 lbs 55.6 kN

This drawing contains confidential information that is property of MacLean Power L.L.C ('MacLean'). Use of MacLean's confidential information without MacLean's express written consent is strictly prohibited and may expose you to legal liability. If you believe that you received this material in error, please destroy it or return it to 'MacLean Power, L.L.C., 7801 Park Place Rd, York, SC, 29745, USA.'

Dimensions: inches [millimeters]

Note: Drawing not actual depiction of insulator appearance



Silicone Rubber Sheath & Sheds  
Complies with applicable ANSI and IEC standards.